

Product data sheet for uvex rubiflex S NB35SF



MADE IN GERMANY 

Manufacturer address

UVEX SAFETY Gloves GmbH
Elso-Klöver-Str. 6
D-21337 Lüneburg
uvex-safety.de

This chemical protection glove features a double cotton-interlock lining. This means that the rubiflex SNB35SF is suitable for a wide range of applications that require chemical protection in addition to increased mechanical protection to heat and cold. The uvex rubiflex S NB35SF is particularly suited to damp, cold and dry working conditions, but can also be used when working with contact heat up to 250°C.

Material number	60209
Sizes	8,9,10,11
Standard	EN ISO 21420:2020, EN 388:2016 + A1:2018, EN ISO 374-1:2016 + A1:2018, EN ISO 374-5:2016, EN 407:2020, EN 511:2006
Standard	EN 388:2016 + A1:2018: 2121X, EN ISO 374-1:2016 + A1:2018: JKNOPT, EN ISO 374-5:2016: bac/fungi, EN 407:2020: X2XXXXX, EN 511:2006: 111
Test chemicals	n-Heptane (J), Sodium hydroxide 40% (K), Acetic acid 99% (N), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T)
Performance classes in accordance with EN 388	2 1 2 1 X
Performance classes in accordance with EN 407	X 2 X X X X
Performance classes in accordance with EN 511	1 1 1
Outer material	Cotton interlock
Coating	NBR
Type	With gauntlet
Colour	Green
Glove length	35 cm