

Product datasheet

uvex 2 6508 1-4

Safety shoe DIN EN ISO 20345:2022+A1:2024 S3L FO LG SC SR

Sizes: 35 - 52 | Width: 10, 11, 12, 14



AREA OF APPLICATION

Medium applications usually alternate between indoor and outdoor areas, meaning that the demands on the robustness of the outsole of a safety shoe are much higher.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES		
Upper material	<ul style="list-style-type: none"> breathable microvelour (clima zone) water-repellent (WPA) suitable for people allergic to chrome textile distance mesh lining for comfortable foot climate 	
Lining material	<ul style="list-style-type: none"> elastic laces 	
Fastening	<ul style="list-style-type: none"> foamed PU heel basket for additional stability in the shoe 	
Heel basket	<ul style="list-style-type: none"> for increased visibility even in dark working environments 	
Reflecting elements	<ul style="list-style-type: none"> soft padding on collar 	
Comfort	<ul style="list-style-type: none"> sizes 35-40 have been produced using a women's last dust tongue removable comfortable innersole 	
Innersole		
PROTECTIVE FEATURES		
Toe cap	<ul style="list-style-type: none"> metal-free protective toe cap 	
Penetration resistance	<ul style="list-style-type: none"> metal-free, textile penetration resistance 	
Scuffcap	<ul style="list-style-type: none"> out of PU for additional protection of the upper material (SC) 	
Ladder grip	<ul style="list-style-type: none"> support on ladders due to transversely inserted profile (LG) 	
CERTIFICATES		
uvex medicare+	<ul style="list-style-type: none"> certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191 	
100% vegan	<ul style="list-style-type: none"> certified free from animal ingredients and products additional protection for people with allergies and intolerances 	
ESD	<ul style="list-style-type: none"> protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1 	
SUSTAINABILITY		
CO ₂ footprint	<ul style="list-style-type: none"> 7.94 kg Cradle-to-Customer (calculation date 02/2026) 	
Recycled/sustainable materials	<ul style="list-style-type: none"> removable innersole made wholly or partly from recycled materials free from harmful substances in accordance with the uvex restricted substances list 	
ACCESSORIES/ SPARE PARTS		
Replacement innersole	<ul style="list-style-type: none"> 9534 7-0 	
Laces	<ul style="list-style-type: none"> black 9599921 	
Elastic laces	<ul style="list-style-type: none"> 9591100 	
Semi-orthopaedic innersoles	tune-up <ul style="list-style-type: none"> low: 95281 medium: 95282 high: 95283 	SECOSOL® COMPLETE+ <ul style="list-style-type: none"> low: 94790 medium: 94791 high: 94792