

Product datasheet

uvex 1 x-craft pro 6800 1-4

Safety shoe DIN EN ISO 20345:2022+A1:2024 S1 PL FO SC SR

Sizes: 35 - 52 | Width: 10, 11, 12, 14



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

TPU outsole uvex x-tended grip planet with 10% recycled granulate from residues



- shock-absorbing and energy-returning uvex i-PUREnri planet midsole with 15% recycled granulate from residues
- **bionom x** – ergonomically designed outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES

Upper material	• durable, robust and flexible PUtek upper material in the forefoot area • breathable, lightweight and tear-resistant ripstop upper material • suitable for people allergic to chrome
Lining material	• textile distance mesh lining for comfortable foot climate
Fastening	• elastic laces
Heel basket	• foamed heel basket out of PU for additional stability in the shoe
Reflecting elements	• for increased visibility even in dark working environments
Comfort	• soft padding on collar • sizes 35-40 have been produced using a women's last • perforated tongue foam for increased breathability (clima zone)
Innersole	• removable comfortable innersole

PROTECTIVE FEATURES

Toe cap	• metal-free protective toe cap
Penetration resistance	• metal-free, textile penetration resistance
Scuffcap	• out of PU for additional protection of the upper material (SC)

CERTIFICATES

uvex medicare+	• certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191
100% vegan	• certified free from animal ingredients and products • additional protection for people with allergies and intolerances
ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1

SUSTAINABILITY

CO ₂ footprint	• 7.14 kg Cradle-to-Customer (calculation date 10/2025)
Recycled/sustainable materials	• midsole, outsole, penetration resistance and removable innersole made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list

ACCESSORIES/ SPARE PARTS

Replacement innersole	• 9579 7-0								
Laces	• black 8446020								
Elastic laces	• 9591300								
Semi-orthopaedic innersoles	<table> <tr> <td>tune-up</td><td>SECOSOL® COMPLETE+</td></tr> <tr> <td>• low: 95284</td><td>• low: 94790</td></tr> <tr> <td>• medium: 95285</td><td>• medium: 94791</td></tr> <tr> <td>• high: 95286</td><td>• high: 94792</td></tr> </table>	tune-up	SECOSOL® COMPLETE+	• low: 95284	• low: 94790	• medium: 95285	• medium: 94791	• high: 95286	• high: 94792
tune-up	SECOSOL® COMPLETE+								
• low: 95284	• low: 94790								
• medium: 95285	• medium: 94791								
• high: 95286	• high: 94792								