

## Product datasheet

### uvex 1 x-craft pro D30® 6806 1-3

Safety shoe DIN EN ISO 20345:2022+A1:2024 S1 PS FO M SC SR

Sizes: 35 - 52 | Width: 10, 11, 12



### AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

### OUTSOLE

Dual-density polyurethane sole



- shock-absorbing and energy-returning uvex i-PUREnri planet midsole with 15 % recycled granulate from residues
- **bionom** x – ergonomically designed PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES		
Upper material	<ul style="list-style-type: none"> <li>• durable and flexible PUtek upper material in the forefoot area</li> <li>• breathable, lightweight and tear-resistant ripstop upper material</li> <li>• suitable for people allergic to chrome</li> </ul>	
Lining material	<ul style="list-style-type: none"> <li>• textile distance mesh lining for comfortable foot climate</li> </ul>	
Fastening	<ul style="list-style-type: none"> <li>• elastic laces</li> </ul>	
Heel basket	<ul style="list-style-type: none"> <li>• foamed heel basket out of PU for additional stability in the shoe</li> </ul>	
Reflecting elements	<ul style="list-style-type: none"> <li>• for increased visibility even in dark working environments</li> </ul>	
Comfort	<ul style="list-style-type: none"> <li>• soft padding on collar</li> <li>• sizes 35-40 have been produced using a women's last</li> <li>• perforated tongue foam for increased breathability (<b>clima</b> zone)</li> </ul>	
Innersole	<ul style="list-style-type: none"> <li>• removable comfortable innersole</li> </ul>	
PROTECTIVE FEATURES		
Toe cap	<ul style="list-style-type: none"> <li>• metal-free protective toe cap</li> </ul>	
Anti-penetration	<ul style="list-style-type: none"> <li>• metal-free, textile penetration resistance (tested with 3 mm test nail)</li> </ul>	
Scuffcap	<ul style="list-style-type: none"> <li>• out of PU for additional protection of the upper material (<b>SC</b>)</li> </ul>	
Metatarsal protection	<ul style="list-style-type: none"> <li>• certified D3O® metatarsal protection up to 100 J (<b>M</b>)</li> </ul>	
CERTIFICATES		
uvex medicare+	<ul style="list-style-type: none"> <li>• certified for orthopaedic innersoles and shoe adjustments according to the description in <b>DGUV 112-191</b></li> </ul>	
100% vegan	<ul style="list-style-type: none"> <li>• certified free from animal ingredients and products</li> <li>• additional protection for people with allergies and intolerances</li> </ul>	
ESD	<ul style="list-style-type: none"> <li>• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1</li> </ul>	
SUSTAINABILITY		
CO <sub>2</sub> footprint	<ul style="list-style-type: none"> <li>• 8.71 kg Cradle-to-Customer (calculation date 10/2025)</li> </ul>	
Recycled/sustainable materials	<ul style="list-style-type: none"> <li>• midsole, penetration resistance and removable innersole made wholly or partly from recycled materials</li> <li>• free from harmful substances in accordance with the uvex restricted substances list</li> </ul>	
ACCESSORIES/ SPARE PARTS		
Replacement innersole	<ul style="list-style-type: none"> <li>• 9579 7-0</li> </ul>	
Laces	<ul style="list-style-type: none"> <li>• black 8446020</li> </ul>	
Elastic laces	<ul style="list-style-type: none"> <li>• 9591300</li> </ul>	
Semi-orthopaedic innersoles	tune-up <ul style="list-style-type: none"> <li>• low: 95284</li> <li>• medium: 95285</li> <li>• high: 95286</li> </ul>	SECOSOL® COMPLETE+ <ul style="list-style-type: none"> <li>• low: 94790</li> <li>• medium: 94791</li> <li>• high: 94792</li> </ul>