

Product datasheet

uvex 1 x-craft 6813 7-0

Perforated safety shoe DIN EN ISO 20345:2022 S1 FO SC SR
Sizes: 35 - 52 | Width: 10, 11, 12, 14



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Dual-density polyurethane sole



- shock-absorbing and energy-returning uvex i-PUREnrj planet midsole with 15% recycled granulate from residues
- **bionom x** – ergonomically designed PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



| FEATURES | | |
|--------------------------------|--|---|
| Upper material | <ul style="list-style-type: none"> • breathable microvelour • suitable for people allergic to chrome | |
| Lining material | <ul style="list-style-type: none"> • textile distance mesh lining for comfortable foot climate | |
| Fastening | <ul style="list-style-type: none"> • elastic laces | |
| Heel basket | <ul style="list-style-type: none"> • foamed heel basket out of PU for additional stability in the shoe | |
| Reflecting elements | <ul style="list-style-type: none"> • for increased visibility even in dark working environments | |
| Comfort | <ul style="list-style-type: none"> • soft padding on collar • sizes 35-40 have been produced using a women's last • perforated tongue foam for increased breathability (clima zone) | |
| Innersole | <ul style="list-style-type: none"> • removable comfortable innersole | |
| PROTECTIVE FEATURES | | |
| Toe cap | <ul style="list-style-type: none"> • metal-free protective toe cap | |
| Scuffcap | <ul style="list-style-type: none"> • out of PU for additional protection of the upper material (SC) | |
| CERTIFICATES | | |
| uvex medicare+ | <ul style="list-style-type: none"> • certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191 | |
| 100% vegan | <ul style="list-style-type: none"> • certified free from animal ingredients and products • additional protection for people with allergies and intolerances | |
| ESD | <ul style="list-style-type: none"> • protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1 | |
| SUSTAINABILITY | | |
| CO ₂ footprint | <ul style="list-style-type: none"> • 7.08 kg Cradle-to-Customer (calculation date 10/2025) | |
| Recycled/sustainable materials | <ul style="list-style-type: none"> • midsole, insole board and removable innersole made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list | |
| ACCESSORIES/ SPARE PARTS | | |
| Replacement innersole | <ul style="list-style-type: none"> • 9579 7-0 | |
| Laces | <ul style="list-style-type: none"> • black 8446020 | |
| Elastic Laces | <ul style="list-style-type: none"> • 9591300 | |
| Semi-orthopaedic innersoles | tune-up <ul style="list-style-type: none"> • low: 95284 • medium: 95285 • high: 95286 | SECOSOL® COMPLETE+ <ul style="list-style-type: none"> • low: 94790 • medium: 94791 • high: 94792 |