

Product datasheet

uvex 1 sport 6890 7-0

Safety sandal DIN EN ISO 20345:2022+A1:2024 S1 FO SC SR

Sizes: 35 - 52 | Width: 10, 11, 12, 14



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing and energy-returning uvex i-PUREnrj planet midsole with 10% recycled granulate from residues
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES		
Upper material	<ul style="list-style-type: none"> • breathable textile • suitable for people allergic to chrome 	
Lining material	<ul style="list-style-type: none"> • textile distance mesh lining for comfortable foot climate 	
Fastening	<ul style="list-style-type: none"> • hook-and-loop fastening 	
Reflecting elements	<ul style="list-style-type: none"> • for increased visibility even in dark working environments 	
Comfort	<ul style="list-style-type: none"> • soft padding on collar • sizes 35-40 have been produced using a women's last • open upper for increased breathability (clima zone) 	
Innersole	<ul style="list-style-type: none"> • removable comfortable innersole 	
Furthermore	<ul style="list-style-type: none"> • metal-free 	
PROTECTIVE FEATURES		
Toe cap	<ul style="list-style-type: none"> • metal-free protective toe cap 	
Scuffcap	<ul style="list-style-type: none"> • out of TPU for additional protection of the upper material (SC) 	
CERTIFICATES		
uvex medicare+	<ul style="list-style-type: none"> • certified for orthopaedic innersoles and shoe adjustments according to the description in DGUV 112-191 	
100% vegan	<ul style="list-style-type: none"> • certified free from animal ingredients and products • additional protection for people with allergies and intolerances 	
ESD	<ul style="list-style-type: none"> • protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1 	
SUSTAINABILITY		
CO ₂ footprint	<ul style="list-style-type: none"> • 7,50 kg Cradle-to-Customer (calculation date 01/2026) 	
Recycled/sustainable materials	<ul style="list-style-type: none"> • midsole, insole board and removable innersole made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list 	
ACCESSORIES/ SPARE PARTS		
Replacement innersole	<ul style="list-style-type: none"> • 9579 7-0 	
Semi-orthopaedic innersoles	tune-up <ul style="list-style-type: none"> • low: 95284 • medium: 95285 • high: 95286 	SECOSOL® COMPLETE+ <ul style="list-style-type: none"> • low: 94790 • medium: 94791 • high: 94792